



Design. Create. Inspire.





At Designflooring, we see flooring differently...

We travel the world in our quest to bring you exceptional floors that inspire and delight. We look to the textures, shapes and formations of the natural world to influence our unique floor designs. By combining these original features with cutting-edge design, we create simply beautiful floors that bring your vision to life.

▽ Gold V15 / 129



▽△ Canadian Urban Oak **R1P816** | 100

Contents

Why Designflooring?	3
A partner you can trust	6
Quality and service	9
Our environmental promise	10
All the benefits of Designflooring	12
Our three product formats	17
Introducing our collection	18
Introducing bespoke design.....	21
Designflooring explained	25
Wood at a glance	26
Stone at a glance	28
Designflooring in commercial environments	31
Sector applications	32
Sector in focus: Hospitality and leisure	36
Sector in focus: Retail	42
Sector in focus: Offices	48
Kaleidoscope:	53
Gluedown wood:	59
Rubens	60
Opus (including Opus Enhance)	64
Van Gogh	68
Art Select	72
Gluedown stone:	77
Rubens	78
Opus (including Opus Enhance)	82
Loose lay wood:	87
Designflooring LooseLay	88
Designflooring LooseLay Longboard.....	88
Loose lay stone:	93
Designflooring LooseLay	94
Rigid core wood:	99
Korlok	96
Palio Core	100
Rigid core stone:	109
Korlok	110
Palio Core.....	114
Resources:	119
Digital tool suite	120
Sample service	122
Cleaning and maintenance	122
Get in touch	123
Product overview	125
Products by range wood	126
Products by range stone	128
Solid colours	129

A partner you can trust

Founded in 2004, Designflooring has grown to be one of the leading vinyl flooring companies in Europe.

Still family owned, we remain true to our roots in being fiercely committed to our customers. Since our beginnings, we have developed our technology, extended our design portfolio and expanded the team.

Our goal remains the same: to create exceptional floors that capture every intricate detail of wood and stone to the highest level of quality that is both practical and beautiful.



▽ Bleached Grey Walnut WP329 | 64





△ ▽ ■ Storm Oak RL12 | 72



▷ Grey V19 | 129



Quality and service

Our distribution centre in Homburg, Germany, provides access to in excess of 200,000m² of our Designflooring products. We pride ourselves on our 99.9% stock holding capability to ensure the product you order is delivered in full and on time.

All of our products are manufactured to ISO 9001. Our robust quality control systems ensure that our products reach their final destination in top condition. In addition, our experienced technical service team are on hand to support you through the specification, installation and maintenance of your chosen design.

To help you get started we offer a sample service for both swatch and full size plank or tiles, together with supporting marketing collateral on your chosen format or by sector.

For more information on how to order a full sized sample, contact your local representative or call our customer service team on:

Designflooring

T: +44 1386 820105

F: +44 1386 820132

E: info@designflooring.com

Designflooring GmbH

T: 0211 469 59203

F: 0211 469 59204

E: verkauf@designflooring.com

Designflooring SAS

T : 01 57 32 39 13

F : 01 57 32 39 14

E: ventes@designflooring.com

Designflooring Nederland

T: 020 200 8282

F: 020 200 8386

E: verkoop@designflooring.com

Our environmental promise


At Designflooring, our goal has always been to produce the best looking and performing luxury vinyl floors with the lowest possible impact on the environment. From the manufacturing of our products to our adhesives, our floors have numerous environmentally friendly properties and certifications to address your project needs.

Our products are 100% phthalate free.

We meet the BRE Global Guide to specification, falling into a generic A/A+ rating for use in health, education, commercial, retail and domestic sectors.

Our products are certified to Indoor 'Air Comfort Gold standard' with FloorScore® Indoor Air Quality certification.





Specify sustainably

Our aim is to remain the leading supplier of LVT flooring and to have a market-leading environmental record of achievement. Through the development of sustainable products and processes, our flooring is manufactured in factories certified to the ISO 14001 Environmental Standard and ISO 9001 Quality Standard. Our products contain up to 50% recycled material in the backing layers taken from post-production waste (off-cuts, trimmings and process dust). Almost 100% of this production and post-production waste is granulated and recycled back into a new plank or tile.

Reducing our environmental impact

Our flooring has an Environmental Product Declaration (EPD). Based on the Life Cycle Assessment (LCA), this evaluates a product's environmental impact in association with the following potential factors:

- Global warming
- Ozone depletion
- Fossil fuel depletion.

Our steps to sustainability:

Sustainable raw materials

The PVC in our products is derived from a truly sustainable resource: salt. We source from ISO 14001/ISO 9001 certified raw material suppliers where possible.

Safe products

All our products are free from:

- Heavy metals and comply with 'REACH' (Registration, Evaluation, Authorisation and Restriction of Chemicals)
- 'BPA' (bisphenol A) and formaldehyde.

None of our products contain raw materials that are reprotoxic, endocrine disrupting or carcinogenic.

Air quality

Tested for contribution to indoor air quality, our products are very low emitting in terms of VOCs (volatile organic compounds), meeting the strictest standards for air quality.



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

All the benefits of Designflooring

From large commercial environments to small residential rooms, at Designflooring, our vast range of products offer the essential benefits that make our luxury vinyl flooring the perfect choice for any flooring space.

△ Azure V12 | 129



△△ Grey Lined Oak KP138 | 60



Durable

Unlike other flooring alternatives, Designflooring gives you the look and feel of natural products but with the durability and resilience of luxury vinyl.



K-Guard+

We use K-Guard+ surface technology for scuff and stain resistance ensuring there is no need to apply an additional surface treatment following installation.



Guarantee

All Designflooring floors come with a commercial guarantee of 10-17 years, depending on the product range specified.



Realistic designs

Inspired by nature, our products are designed in-house and realistically replicate the look and feel of wood and stone materials.



Waterproof

Unlike laminate and engineered hardwoods, our floors are impervious to water and will not swell, crack or warp when wet, making them perfect for kitchens, office tea points and washrooms.



Hygienic

Our floors don't hold dust, dirt, pollen or other allergens. Our cleaning products also kill 99.9% of germs.



Low maintenance

The commercial cleaning and maintenance regime is simple and can be carried out by hand or using a mechanical cleaning apparatus. With Designflooring, you don't have to worry about any sanding, refinishing, staining or varnishing either.



Acoustic qualities

Designflooring is quieter underfoot compared to most hard flooring alternatives. Our rigid core and loose lay collections come with a backing that reduces noise transfer to rooms below, making it ideal for apartment blocks and any upstairs rooms.



100% recyclable

We do everything we can to meet and exceed legislative and environmental guidelines in all regions. All Designflooring floors are 100% recyclable and are environmentally friendly.



Compatible with underfloor heating

For added warmth, our flooring is perfectly suitable for underfloor heating systems up to 27°C.



Slip resistance

Slip resistant flooring helps to prevent accidents caused by trips, slips and falls in busy environments. Our products have a slip rating of either R10 or R11. See page 61 - 115 for details.







△▽ Argento SP217 / 82

Our three product formats


Gluedown, loose lay and rigid core.

▽ Azure V2 | 129

Gluedown

Our gluedown collection offers our widest choice of colours and formats. Features such as textured emboss, wide bevels or flat edges make each range unique to Designflooring.

We offer a wide selection of sizes: from the 228,6mm x 76,2mm planks of Art Select parquet to the large 1219,2mm x 177,8mm planks in Opus. Plus, tiles ranging from 304,8mm x 457,2mm in Rubens to Opus's 457,2mm x 609,6mm tile.



Loose lay


Designflooring LooseLay features our K-Wave friction grip backing, which holds the product to the subfloor in conjunction with Designflooring tackifier. Ideal for locations where underfloor access is required, or a temporary floor covering such as pop up shops and exhibitions. Designflooring is quick and easy to install.

Designflooring LooseLay:

1050,0mm x 250,0mm planks, 500,0 x 610,0mm tiles

Designflooring LooseLay Longboard:

1500,0mm x 250,0mm




Rigid core

Korlok and Palio Core, are ideal for installations where acoustics, uneven subfloors or preservation of existing hard floors need to be considered. Its click-locking mechanism allows for quick installation and the pre-attached acoustic backing eliminates the need for a separate underlayment.









Korlok: 1420,0mm x 225,0mm planks,
457,0mm x 600,0mm tiles

Palio Core: 1220,0mm x 179,0mm planks,
307,0mm x 600,0mm tiles.



Introducing our collection

Featured below is a quick reference guide including key product details like different size and style variants on offer. See our product format section on page 17 for more information.

	Range	EN685/ EN ISO10874	Commercial Guarantee*	Wear Layer (mm)	Thickness (mm)	Plank Size (mm)	Tile Size (mm)
GLUEDOWN		31: Commercial moderate, 23: Domestic heavy	10 years**	0,3	2	914,4 x 152,4 1219,2 x 177,8 457,2 x 76,2	304,8 x 457,2
		42: Light industrial general, 33: Commercial moderate, 23: Domestic heavy	15 years	0,55	2,5	914,4 x 152,4 1219,2 x 228,6	457,2 x 609,6
		42: Light industrial general, 33: Commercial moderate, 23: Domestic heavy	15 years	0,55	2,5	914,4 x 152,4 1219,2 x 228,6	457,2 x 609,6
		42: Light industrial general, 33: Commercial moderate, 23: Domestic heavy	15 years	0,55	3	1219,2 x 177,8	N/A
		43: Light industrial general, 34: Commercial moderate, 23: Domestic heavy	20 years	0,7	3	228,6 x 76,2 914,4 x 152,4 1219,2 x 177,8	N/A
		Dependent on ranges chosen	10 years**	With over 100 different colours to choose from, the precise technical specification for your Kaleidoscope product will depend on your final selection. Please contact your business manager for further details.			
LOOSE LAY		42: Light industrial general, 33: Commercial moderate, 23: Domestic heavy	15 years	0,55	4,5	1050,0 x 250,0 1500,0 x 250,0	500,0 x 610,0
RIGID CORE		33: Commercial moderate, 23: Domestic heavy	15 years	0,55	6,5	1420,0 x 225,0	457,0 x 600,0
		33: Commercial moderate, 23: Domestic heavy	15 years	0,55	6,5	1220,0 x 179,0	307,0 x 600,0

* Subject to terms. Please see our website. ** Commercial Light Duty use only.



Fábrica WP419 | 64



△ ■ Distressed Oak **VGW82T**, French Oak **VGW85T**, Honey Oak **VGW94T*** | 68



▽ ■ Pate Lined Oak **KP094**, Grey Lined Oak **KP138**, Washed Scandi Pine **KP132** | 60, Cumbrian Stone **ST14*** cut to bespoke size

△ ■ Black Riven Slate **ST15**, Honed Oyster **ST17** cut to bespoke size | 78



△ ■ Mico **SP217*** and ■ Aged Oak **KP98***



▽ Gold **V15** | 129

*Product designs can be viewed on our website www.designflooring.com

Introducing bespoke design

Flexible and versatile, our flooring will complement and enhance your interior design, helping you to create inspirational spaces that will 'wow', intrigue and inspire social sharing.

Our floor collections offer infinite shape, size, colour and texture combinations to achieve a statement look that is individual to your project. Embracing the versatility of our flooring, your design can reflect the uniqueness of the local environment.

Combining designs can bring a modern interpretation of traditional style to your project. For example, why not mix and match a rich oak design with contemporary grey slate in a bold geometric pattern to give character and quirkiness to your space.

Complementary or contrasting designs can effortlessly create a unique interior.

Our Kaleidoscope collection of geometric shapes create eye-catching patterns. A subtle yet sophisticated effect can be created with a combination of complementary wood shades in hexagon tiles. Alternatively, an impactful 3D pattern can be achieved with a combination of dark and light shades.

With Designflooring there are no limits.






▽ **Luna SP117***, **Urbus SP213**, **Ombra SP114*** | 82

▽ **Pale Lined Oak KP54**, **White Painted Oak KP105** | 60

▽ **Carrara T90***



▽ **Mid Worn Oak KP103**, **Light Worn Oak KP104**, **White Painted Oak KP105** | 60


*Product designs can be viewed on our website www.designflooring.com



▽ White Washed Oak **VEW80T**, Ebony **VEW89T** | 68



△ Cubix: **Canberra LM0e***, Corris **LM22***, Fiore **LM16***



▽ **Pale Limed Oak KP95**, **Limed Washed Oak KP99**, **Grey Limed Oak KPI38**, **Washed Scandi Pine KPI32** | 60 and **Cumbrian Stone ST14*** cut to bespoke size





▷ Taupe V17 | 12p

*Product designs can be viewed on our website www.designflooring.com

Designflooring explained

There are endless design possibilities for Designflooring in commercial and retail environments. The beauty of Designflooring is that it is so versatile.

Take any of our products and with a little imagination, create your own design. Once you've selected a floor, you can define the space and add interest with our designflooring elements.

By integrating borders, design strips and special cuts, you can add definition to your space such as a rug effect or walkways to help guide customers, or simply a method of zoning a large space.

Design strips and borders

Design strips can be placed between tiles to create a natural grouting effect or to enhance the design of the floor. Choose from a wide range of tones and textures, available in 3, 5 and 10mm widths.

Design features

Commercial projects that require personalisation, for example, including a company logo or motif can be achieved with our custom cuts design service.

Wood at a glance


■ Art Select |
 ■ Van Gogh |
 ■ Opus |
 ■ Rubens |
 ■ Designflooring LooseLay |
 ■ Korlok |
 ■ Palio Core

 ■ LLP311	 ■ KP132	 ■ SM-KP132	 ■ WP419	 ■ WP422	 ■ LLP304	 ■ KP137
 ■ KP105	 ■ VGW80T	 ■ KP133	 ■ KP131	 ■ RCP6508	 ■ WP421	 ■ WP418
 ■ LLP95	 ■ LLP149	 ■ RKP8105	 ■ WP420	 ■ PVP147	 ■ KP138	 ■ SM-KP138
 ■ KP136	 ■ LLP306	 ■ LLP92	 ■ KP135	 ■ RKP8113	 ■ WP423	 ■ LLP142
 ■ PVP149	 ■ LLP147	 ■ KP99	 ■ SM-KP99	 ■ KP95	 ■ SM-KP95	 ■ VGW94T
 ■ KP139	 ■ RKP8108	 ■ WP411	 ■ RKP8103	 ■ PVP144	 ■ RKP8116	 ■ LLP150
 ■ VGW84T	 ■ LLP108	 ■ LLP101	 ■ RCP6510	 ■ LLP307	 ■ VGW81T	 ■ RCP6504
 ■ RKP8117	 ■ LLP145	 ■ VGW85T	 ■ LLP317	 ■ RL01	 ■ LLP109	 ■ KP94
 ■ LLP144	 ■ LLP113	 ■ PVP145	 ■ VGW52T	 ■ RL02	 ■ VGW86T	 ■ LLP102
 ■ LLP310	 ■ AP01	 ■ RKP8111	 ■ LLP305	 ■ RCP6501	 ■ EW03	 ■ VGW102T




Opus Enhance

A number of our Opus products are available with an enhanced finish and rougher surface texture, specifically for use in commercial areas. Look out for the R11 logo on relevant products. See pages 64 and 82 for details.




Stone at a glance

■ Opus | ■ Rubens | ■ Designflooring LooseLay | ■ Korlok | ■ Palio Core



Solid colours



KaleidSCOPE

Looking for something different?
Kaleidoscope offers a range of shapes, patterns
and colourways to create a visual 3D impact.

▷ Volcanic Black RKT2406 1110





▽ ■ Argento **SP217**, Argento **SM-SP217*** | 82

△ ■ Urbus **SP213**, Nero **SP115*** | 82



△ ■ Storm Oak **AP07**, Storm Oak **RI12** | 72



▷ Dove Grey MP | 129

*Product designs can be viewed on our website www.designflooring.com

Designflooring in commercial environments

At Designflooring, we understand the need to create a commercial environment that not only leaves a lasting impression, but also creates a space that will promote constant engagement. Below we explore a range of techniques that can be created using our designs:

Zoning

Our wood and stone designs can be fitted alongside other flooring types, such as carpet, to create zones and areas of interest. In healthcare, for example, zoning will help to provide necessary colour contrast for the visually impaired to distinguish one key area from another.

Wayfinding

The unparalleled flexibility of our flooring allows you to add walkways to assist navigation through a retail shop, mall or healthcare environment for example. In retail, it is beneficial to create paths in the floor to lead customers around the store.

Blending

Match texture and colour to create a tonally blended floor. You can use this technique to update an existing floor without having to replace every plank or tile. To ensure design compatibility, select planks or tiles from the same collection to achieve a look that is both impressive and unique.

Sector applications

Retail

Whether a small boutique or large superstore, eye-catching floor designs that guide consumers through the space are essential. Our unique design capabilities allow for the creation of zoning and wayfinding.

Education

Designflooring's durable and low maintenance flooring helps you to create safe and inspiring educational environments for students of all ages.

Healthcare

Cleanliness and durability are vital in the healthcare sector. With Designflooring, you can have a durable, easy to maintain floor that creates a comfortable environment.

Hospitality and leisure

In a sector where style, resilience and low maintenance are vital, Designflooring is a proven choice for the demands of hotels, bars, restaurants, tourist attractions and leisure facilities.

Office


Offices are places for thought, discussion and creativity. Choosing Designflooring for the boardroom, reception or office provides a space that's comfortable, inspiring and practical.

Housing

Quality flooring adds value to new housing and co-living developments. Designflooring provides a hard wearing, comfortable solution that will stand the test of time year after year.

◀ Lace V20 | 129

* Product designs can be viewed on our website
www.designflooring.com





△ Columbia WP222 | 64


△ Fumo SP216 | 82



△ Avena WP423 | 64

△ Raven Oak LLP302 | 88

▽ Grey Limed Oak SM-KP138 SM-KP138 | 60



△ Hessian Oak VGP23T





Sector in focus:


Hospitality and leisure

Designed for hospitality and leisure

Making a positive first impression and creating a space that sparks an emotional connection is key for hoteliers. Whether the objective is to create a feeling of 'home-from-home' in unprecedented luxury or a quirky location, the goal is the same: to meet and surpass guests evolving expectations.

The desire for 'insta-worthy' interiors has dominated trend reports in the last few years, influencing styles that create a unique experience.

Creating something that is totally personal and individual to a space adds a layer of personality that helps create an individual identity.



△ ■ Lutum SP218 | 82



△ ■ Luna SP111* - Nero SP15*





▽ Terracotta **VT8** | 129

*Product designs can be viewed on our website www.designflooring.com



△ ■ Pallida **WP418** | 64



△ ■ Ignea **WP313** | 64

Where style combined with resilience and longevity is vital, Designflooring is a proven choice for the demands of hotels, bars, restaurants, tourist attractions and leisure facilities.

Designed with commercial settings in mind, our portfolio of patterns, textures and styles have been made with enhanced slip resistant ratings and acoustic absorbency. Products like Korlok include a pre-attached acoustic foam backing that not only eliminate the need for underlay but also helps to reduce impact noise transfer by 21dB, making it perfect for hotel bedrooms and conference rooms above ground level. Whilst our Opus Enhance range has achieved an R11 slip resistance rating offering further protection in more vulnerable areas such as hotel lobby and reception areas. All offered without any compromise on the natural embosses that a Designflooring floor is known for.

ió Contemporary Wellness Centre, Marseille

Create a calm atmosphere with warm tones combined with natural oak grains for an attractive and modern finish.

△ Blush V14 | 129





▲ Country Oak **LP92** / 68

"With more than 200 visitors per week, we needed the realistic look of natural wood, but with the practical advantages of a LVT flooring."

*Mrs. Bénédicte Morel, owner of
io Contemporary Wellness Centre*

Go bold...

...with a stark monochromatic palette enhanced by custom-cut geometric shapes to create a look that's totally unique.

△ Gold v15 | 129





▲ Luna SP111 and Nero SP115*

*Product designs can be viewed on our website www.designflooring.com

Sector in focus:

Retail


Designed for retail

A Designflooring floor offers a hard wearing and practical choice for high footfall stores. The extensive range of wood and stone designs offers the customer great choice when choosing their floor.

We combine the natural beauty of wood and stone with cutting edge design to bring you exceptional floors that will look stunning for years to come. Each plank or tile is carefully designed for authenticity, featuring all the subtle textures and features of the real thing.

A unique design can be easily created with a combination of laying patterns and borders, special cut shapes or logos, all selected from your favorite wood and stone designs.

Our floors are warmer and quieter than other materials, reducing the likelihood of fatigue for your customers and staff. While a robust wear layer gives a durable surface that stands up to high levels of footfall. Not only that, an enhanced K-Guard+ surface treatment offers protection from damage that can spoil the look of your floor over time as well as making it easier to clean.



▽ Country Oak VGW81T and Aged Redwood VGW100T | 68



△ Pale Lime Oak Kpp4, Lined Washed Oak Kpp9, Grey Lined Oak Kp138, Washed Scandi Pine Kp132 | 60 and Cumbrian Stone S714 - cut to bespoke size



△ ■ Grey Limed Oak **KP138** | 60

▽ Laurel **V13** | 129



△ ■ Fumo **SP216** | 82



*Product designs can be viewed on our website www.designflooring.com

We understand the importance of minimising the disruption of a refurbishment to busy retail environments, which is why our floors are simple and convenient to fit. Our innovative LooseLay and Korlok products can be fitted over existing hard floors, reducing business downtime.

What's more, the flexible format of a Designflooring floor lends itself well to partial area refitting; perfect for introducing a rug effect for a quick refresh, or to remain on-trend and in-line with seasonal displays.

Available in both wood and stone designs, LooseLay and LooseLay Longboard can be fitted with little disruption and is easy to lift and replace when necessary. Its innovative K-Wave friction grip backing creates a strong bond to the subfloor using a combination of weight and friction. Perfect for temporary areas or pop-up stores, a LooseLay floor can be quickly taken up and refitted at other locations.

With a comprehensive guarantee against manufacturing (see range details page 18 for warranty details) you can be confident that Designflooring is designed to last.

Berendowicz & Kublin Barber, Katowice

Kaleidoscope fitted in a rug effect, gives character and individuality not only to the floor but the entire interior.

△ Teupe V17 | 129





△ Cubix: ■ Canberra **LM06***, Corris **LM22***, Fiore **LM16*** cut to bespoke size

"It's not an exaggeration to say that the flooring is the main element that makes the salon a truly memorable space."
Agata Chomiak, interior designer

*Product designs can be viewed on our website www.designflooring.com

Mix it up...

...in open plan spaces, a mix and match combination of planks can create an eye-catching floor and identity.

△ Dove Grey V19 / 129





△ **Pale Lime Oak KP94**, **Limed Washed Oak KP99**, **Grey Limed Oak KP138**, **Washed Scandi Pine KP132**, **60 and Cumbrian Stone ST14*** cut to bespoke size

*Product designs can be viewed on our website www.designflooring.com

Sector in focus:

Offices

Designed for offices

A great first impression for any business looking to bring customers to their premises is important to uphold brand reputation, win or retain customers.

A welcoming and professional environment helps forge good business relations. Our collection of flooring offers a practical solution that is perfect for busy office environments, is hygienic and easy to maintain.

On top of this, it's also designed to reduce ambient sound, making it quieter than hard floors; ideal for board room settings or open plan buildings.



▽ Avena WP423 | 64



△ Columba WP422 | 64





△ ■ Antique Timber **LLP106** | 88

▽ Baby Blue **V13** | 129



△ ■ Alaska **LLT215**, Vermont **LLT217** | 94



Designflooring is a proven choice for offices where the movement of furniture and chairs can impact the appearance of the floor over time. Our K-Guard+ surface protection eliminates the need for an additional surface treatment once installed, making it durable, easy to maintain and looking stylish for years to come.

An enhanced slip resistance provides added safety, particularly in reception areas prone to surface water.

The high acoustic absorbency of our rigid core and LooseLay ranges contribute to a calm and productive working environment. Both quick to install means there is little downtime for businesses during installation.

All Designflooring product have a generic A/A+ BRE Global rating meeting the best environmental performance for materials.

Schindler, France

Make a great first impression with Designflooring LooseLay when welcoming visitors and customers to new premises.

△ Crimson V16 | 29







▲ ■ Antique Timber **LIPiE** | 88

"Designflooring has a strong reputation in Europe for supplying a wide range of luxury vinyl flooring in various applications," explains Mr Cédric Bordet, CEO of Soft Building Patrimony.



Kaleidoscope

Kaleidoscope is a unique collection of wood, stone and solid colours available in geometric designs including Cubix, Pennon and Apex. Kaleidoscope offers the design community unparalleled flexibility at the point of specification.



Apex





Hexa





Pyramid





Cubix





Pennon



Half Pennon



Tripoint



Individual shapes are cut from original Designflooring products so that they retain our authentic designs and key technical specification including slip resistance and wear layer. With over 100 different colours to choose from, the precise technical specification for your Kaleidoscope product will depend on your final selection. Please contact your business manager for further details on how to order.

Kaleidoscope set designs: We also offer a range of Kaleidoscope products which have smaller dimensions and shorter lead times to suit a smaller environment.



Pyramid KAL01



Cubix KAL02



Cubix KAL03




Pennon KAL04



Pennon KAL05



Apex KAL06



Apex KAL07



Hexa KAL08




Hexa KAL09



Tripoint KAL10



Cubix KAL13




Apex KAL14



△ Pennon using ■ Washburn LM07*, Fiore LM16*, Corris LM22*

△▽ Apex using ■ Pale Lined Oak KP94, Mid Worn Oak KP103 | 60



△▽ Bespoke Pattern Using ■ Spirito LST04* | ■ Corris LM22*, Washburn LM07*, Fiore LM16*



Kaleido
SCOPE
GLUEDOWN

*Product designs can be viewed on our website www.designflooring.com

Rubens Wood

Our Rubens collection is the perfect partner for the housebuild sector. With an array of colours including rustic, lime washed, and white painted looks in standard, slim and herringbone sizes, this collection offers versatility and room to room combinations.

914,4mm x 152,4mm



Pale Limed Oak **KP94**



Washed Sawn Oak **KP134**



Rose Washed Oak **KP95**




Soft Sawn Oak **KP135**



Lime Washed Oak **KP99**



Coastal Sawn Oak **KP136**



White Painted Oak **KP105**




Clay Sawn Oak **KP137**



Grey Scandi Pine **KP131**



Grey Limed Oak **KP138**



Washed Scandi Pine **KP132**



Raw Spotted Gum **KP139**



Natural Scandi Pine **KP133**



Nickel Spotted Gum **KP140**

457,2mm x 76,2mm



Rose Washed Oak **SM-KP95**


























Lime Washed Oak **SM-KP99**



Washed Scandi Pine **SM-KP132**



Grey Limed Oak **SM-KP138**

	Standard	Result
	EN ISO 24342	See page opposite
	EN ISO 24346	2,0 mm
	EN ISO 24340	0,3 mm
	Surface treatment	K-Guard+ PU coating
	Light industrial	n/a
	Commercial	10 years
	Residential	30 years
		No
	EN ISO 23997	3605 g/m ²
	EN 649 / EN ISO 10582	Heterogeneous PVC
	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	n/a 31: Commercial moderate 23: Domestic heavy
	EN 13501-1	Bfl-s1
	EN ISO 26987 / EN 423	Excellent
	EN ISO 105-B02	≥6
	EN 649 EN ISO 10582	Group T Type 1
	EN ISO 24344	Pass
	EN 434 / EN ISO 23999	≤0,25%
	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 1 dB
	EN 1815	Pass
	EN 433 / EN ISO 24343-1	Pass ≤0,1 mm
	EN 425 / EN ISO 4918	Pass
	ISO 8302	0,0084 m ² K/W Suitable for underfloor heating. Max 27°C
	DIN 51130 EN 13893	R10 DS
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.
	French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
	Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature	Yes
	Pressure Sensitive	Yes
		Suitable
		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.





Rubens
GLUEDOWN



△ ▽  Grey Scandi Pine KPT31 | 90

Opus Wood

Our fresh, modern collection Opus combines flexible layout options, stylish design and durability. With two planks to offer versatility. Designed with commercial spaces in mind, our Opus Enhance products have a rougher surface texture, proven to improve slip resistance. Look out for the R11 logo on individual product pages for more detail.

1219,2mm x 228,6mm



Niveus **WP411** | **WP411-SR**



Stratis **WP420**



Magna **WP413** | **WP413-SR**



Rubesco **WP421**



Argen **WP414**



Columba **WP422** | **WP422-SR**



Pallida **WP418**



Avena **WP423** | **WP411-SR**



Fabrica **WP419**

914,4mm x 152,4mm



Ignea **WP313** | **WP313-SR**



Warm Walnut **WP327**



Bleached Grey Walnut **WP329**


























Tenebra Walnut **WP330**

Opus Enhance

Designed with commercial spaces in mind, our Opus Enhance products have a rougher surface texture, proven to improve slip resistance and have a R11 slip rating.



	Standard	Result
 Size	EN ISO 24342	See page opposite
 Thickness	EN ISO 24346	2,5 mm
 Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee*	Light industrial Commercial Residential (Not applicable to Opus Enhance)	10 years 15 years 30 years
 Bevelled edge		Micro
 Mass	EN ISO 23997	4398 g/m ² (Opus Enhance: 4270 g/m ²)
 Standards	EN 649 / EN ISO 10582	Heterogeneous PVC
 Classification	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987 / EN 423	Excellent
 Light fastness	EN ISO 105-B02	≥6
 Abrasion resistance	EN 649 EN ISO 10582	Group T Type 1
 Flexibility	EN 434/EN ISO 23999	Pass
 Dimensional stability	EN 434 / EN ISO 23999	≤ 0,25% (Opus Enhance: Pass)
 Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 2 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN ISO 24343-1	Pass ≤0,1 mm
 Castor chair continuous use	EN 425 / EN ISO 4918	Pass
 Thermal resistance	ISO 8302	0,0097 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance**	DIN 51130 EN 13893	R10 (Opus Enhance: R11) DS
 Environmental	Indoor Air Comfort	Gold certification
	French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0	Compliant low emitting VOC emissions. A+
	Environmental Product Declaration (Not applicable to Opus Enhance)	Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
 Adhesive	Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature	Yes
	Pressure Sensitive	Yes
UPEC Classification QB UPEC Certification	QB 30	U3P3E2C2 n°788/354-001.1 For products supplied into France only.
 Recycling		Suitable
 Phthalate free		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



▷△ ■ Grano WP311 and Ignea WP313 | 64





Opus
GLUEDOWN

Opus
ENHANCE
GLUEDOWN

Van Gogh Wood

The designs and textures incorporated in our Van Gogh collection are highlighted by a variety of beautiful effects, including distressed, reclaimed and limed woods. Large plank sizes, distinctive grain detail and a subtle texture create a look that works in any space.

1219,2mm x 177,8mm



Auckland Oak **VGW52T**



White Washed Oak **VGW80T**



Country Oak **VGW81T**



Distressed Oak **VGW82T**



Frosted Birch **VGW83T**



Birch **VGW84T**



French Oak **VGW85T**



Classic Oak **VGW86T**



Ebony **VGW89T**


























Honey Oak **VGW94T**



Aged Redwood **VGW100T**



Charred Oak **VGW102T**

	Standard	Result
 Size	EN ISO 24342	1219,2 mm x 177,8 mm
 Thickness	EN ISO 24346	3,0 mm
 Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee*	Light industrial Commercial Residential	10 years 15 years 30 years
 Bevelled edge		Micro
 Mass	EN ISO 23997	5187 g/m ²
 Standards	EN 649 / EN ISO 10582	Heterogeneous PVC
 Classification	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B _f -s1
 Staining resistance	EN ISO 26987 / EN 423	Excellent
 Light fastness	EN ISO 105-B02	≥7
 Abrasion resistance	EN 649 EN ISO 10582	Group T Type I
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN 434 / EN ISO 23999	≤0,25%
 Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 4 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433 / EN ISO 24343-1	Pass ≤0,1 mm
 Castor chair continuous use	EN 425 / EN ISO 4918	Pass
 Thermal resistance	ISO 8302	0,0118 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance**	DIN 51130 EN 13893	R10 DS
 Environmental	Indoor Air Comfort French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
 Adhesive	Universal Acrylic Epoxy High Temperature Pressure Sensitive	Yes Yes Yes Yes Yes
 Recycling		Suitable
 Phthalate free		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



▷△ ■ Country Oak VGW81T | 68





GLUEDOWN
Van Gogh

Art Select Wood

Our premium Art Select wood collection is made up of our most intricate designs combined with detailed embossing techniques and elegant bevelled edges. We've taken inspiration from around the world to produce a collection that embodies luxury, sophistication and versatility.

Oak Royale

1219,2mm x 177,8mm



Spring Oak **RL01***



Summer Oak **RL02**



Storm Oak **RL12**

Handcrafted

914,4mm x 152,4mm




Hickory Nutmeg **EW03**

Parquet

228,6mm x 76,2mm


























Blond Oak **AP01***



Storm Oak **AP07**

* RL01 and AP01 are the same colour design

	Standard	Result
 Size	EN ISO 24342	See page opposite
 Thickness	EN ISO 24346	3,0 mm
 Wear layer	EN ISO 24340	0,7 mm
Surface treatment		K-Guard+ PU coating
Guarantee*	Light industrial Commercial Residential	15 years 20 years 30 years
 Bevelled edge		Standard
 Mass	EN ISO 23997	5015 g/m ²
 Standards	EN 649 / EN ISO 10582	Heterogeneous PVC
 Classification	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	43: Light industrial heavy 34: Commercial very heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987 / EN 423	Excellent
 Light fastness	EN ISO 105-B02	≥6
 Abrasion resistance	EN 649 EN ISO 10582	Group T Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN 434 / EN ISO 23999	≤0,25%
 Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 2 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433 / EN ISO 24343-1	Pass ≤0,1 mm
 Castor chair continuous use	EN 425 / EN ISO 4918	Pass
 Thermal resistance	ISO 8302	0,0147 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance**	DIN 51130 EN 13893	R10 DS
 Environmental	Indoor Air Comfort French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
 Adhesive	Universal Acrylic Epoxy High Temperature Pressure Sensitive	Yes Yes Yes Yes Yes
 Recycling		Suitable
 Phthalate free		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



▷△▽ ■ Spring Oak AP01 | 72





Rubens Stone

Our Rubens tile collection has been handpicked to offer classic pale to contemporary dark slate tones.


304,8mm x 457,2mm

























Black Riven Slate **ST15**



Grey Riven Slate **ST16**



Honed Oyster Slate **ST17**

	Standard	Result
	EN ISO 24342	See page opposite
	EN ISO 24346	2,0 mm
	EN ISO 24340	0,3 mm
	Surface treatment	K-Guard+ PU coating
	Guarantee*	Light industrial Commercial Residential
		n/a 10 years 30 years
	Bevelled edge	No
	Mass	EN ISO 23997 3605 g/m ²
	Standards	EN 649 / EN ISO 10582 Heterogeneous PVC
	Classification	EN 685 / EN ISO 10874: Light industrial Commercial Domestic
		n/a 31: Commercial moderate 23: Domestic heavy
	Reaction to fire	EN 13501-1 Bfl-s1
	Staining resistance	EN ISO 26987 / EN 423 Excellent
	Light fastness	EN ISO 105-B02 ≥6
	Abrasion resistance	EN 649 EN ISO 10582 Group T Type 1
	Flexibility	EN ISO 24344 Pass
	Dimensional stability	EN 434 / EN ISO 23999 ≤0,25%
	Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8 ΔL _w = 1 dB
	Electrical behaviour body voltage	EN 1815 Pass
	Indentation - residual	EN 433 / EN ISO 24343-1 Pass ≤0,1 mm
	Castor chair continuous use	EN 425 / EN ISO 4918 Pass
	Thermal resistance	ISO 8302 0,0084 m ² K/W Suitable for underfloor heating. Max 27°C
	Slip resistance**	DIN 51130 EN 13893 R10 DS
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.
	Environmental	French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration
		A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
	Adhesive	Universal Acrylic Epoxy High Temperature Pressure Sensitive
		Yes Yes Yes Yes Yes
	Recycling	Suitable
	Phthalate free	Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.





△ ▽ **Grey Riven Slate** ST16 | 78

Opus Stone

The contemporary look of Opus is carried across to its stone range. Varying in shades of pale grey and darker tones, these tiles are available in both poured concrete and polished limestone looks. We've also extended our Opus Enhance range to include four designs in our stone collection featuring an increased slip rating, tailored to commercial environments.

457,2mm x 609,6mm



Urbus **SP213** | **SP213-SR**




Ferra **SP215**



Fumo **SP216** | **SP216-SR**



Argento **SP217** | **SP217-SR**





























Lutum **SP218** | **SP218-SR**

Opus Enhance

Designed with commercial spaces in mind, our Opus Enhance products have a rougher surface texture, proven to improve slip resistance and have a R11 slip rating.



	Standard	Result
	EN ISO 24342	See page opposite
	EN ISO 24346	2,5 mm
	EN ISO 24340	0,55 mm
		K-Guard+ PU coating
	Light industrial Commercial Residential (Not applicable to Opus Enhance)	10 years 15 years 30 years
		Micro
	EN ISO 23997	4398 g/m ² (Opus Enhance: 4270 g/m ²)
	EN 649 / EN ISO 10582	Heterogeneous PVC
	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
	EN 13501-1	B _{fl} -s1
	EN ISO 26987 / EN 423	Excellent
	EN ISO 105-B02	≥6
	EN 649 EN ISO 10582	Group T Type 1
	EN 434/EN ISO 23999	<0.25% (Opus Enhance: Pass)
	EN 434 / EN ISO 23999	Pass
	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 2 dB
	EN 1815	Pass
	EN 433 / EN ISO 24343-1	Pass ≤0,1 mm
	EN 425 / EN ISO 4918	Pass
	ISO 8302	0,0097 m ² K/W Suitable for underfloor heating. Max 27°C
	DIN 51130 EN 13893	R10 (Opus Enhance: R11) DS
	Indoor Air Comfort French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration (Not applicable to Opus Enhance)	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
	Universal Acrylic Epoxy High Temperature Pressure Sensitive	Yes Yes Yes Yes Yes
	QB 30	U3P3E2C2 n°788/354-001.1 For products supplied into France only.
		Suitable
		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



▷△ ■ Fumo SP216 | 82





Loose lay wood

Discover our Designflooring LooseLay wood and Longboard range. Both demonstrate the same attention to detail dedicated to our gluedown collection, but with the added versatility of larger plank formats; ideal for large commercial projects.

Designflooring LooseLay Wood & Longboard

With enhanced acoustic properties and excellent environmental credentials, our Designflooring LooseLay wood and Longboard range can be laid over most existing hard floors, with a simple application of Designflooring tackifier.

Our LooseLay Longboard is 1500,0mm long, 42% longer than our standard LooseLay planks, helping to achieve faster installation times and ideal for large open plan living.

1050,0mm x 250,0mm



Palmaria **LLP149**



Torcello **LLP145**



Linosa **LLP148**



Ashland **LLP95**



Providence **LLP108**



Stamford **LLP109**



Lampione **LLP147**



Sicilia **LLP142**



Sardinia **LLP143**



Country Oak **LLP92**



Budelli **LLP146**



Heritage Oak **LLP102**



Tavolara **LLP144**



Levanzo **LLP150**



Hartford **LLP112**



Cambridge **LLP113**



Antique Timber **LLP106**



Vivara **LLP151**



Traditional Oak **LLP101**



Hudson **LLP99**

1500,0mm x 250,0mm



Bleached Tasmanian Oak **LLP311**



Champagne Oak **LLP310**



Pearl Oak **LLP306**



Lemon Spotted Gum **LLP317**



Weathered Heart Pine **LLP304**



Reclaimed Heart Pine **LLP305**



French Grey Oak **LLP308**



Taupe Oak **LLP309**



Twilight Oak **LLP301**



Neutral Oak **LLP307**



Raven Oak **LLP302**



Antique Heart Pine **LLP303**

	Standard	Result
	EN ISO 24342	See page opposite
	EN ISO 24346	4,5 mm
	EN ISO 24340	0,55 mm
		K-Guard+ PU coating
	Light industrial Commercial Residential	10 years 15 years 30 years
		No
	EN ISO 23997	7470 g/m ²
	EN 649 / EN ISO 10582	Heterogeneous PVC
	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
	EN 13501-1	B _{fl} -s1
	EN ISO 26987 / EN 423	Excellent
	EN ISO 105-B02	≥7
	EN 649 EN ISO 10582	Group T Type 1
	EN ISO 24344	Pass
	EN 434 / EN ISO 23999	≤0,10%
	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 13 dB
	EN 433 / EN ISO 24343-1	Pass ≤0,1 mm
	EN 425 / EN ISO 4918	Pass
	ISO 8302	0,0245 m ² K/W Suitable for underfloor heating. Max 27°C
	DIN 51130 EN 13893	R10 DS
	Indoor Air Comfort French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
	Most applications will not require the use of adhesives. However, we recommend the use of a tackifier for heavy traffic areas.	
		Suitable
		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



△ ▽ ■ Pearl Oak LP306 / 88





Karndean
LooseLay

LOOSE LAY

Karndean
LooseLay
Longboard


LOOSE LAY




Designflooring LooseLay Stone

Available in a large-format rectangular tile, Designflooring LooseLay stone is easy to install and features our K-Wave friction grip backing designed to hold products in place in combination with our Designflooring tackifier, without the need for clicking or locking. It also boasts enhanced acoustic properties and is 100% recyclable. Each tile can be lifted individually making it perfect for spaces where access is required for underfloor services.


500,0mm x 610,0mm




Tino LLT208




Seattle LLT214



Alaska LLT215



Capri LLT209




Quebec LLT219




Ontario LLT218



Utah LLT216



Indiana LLT202



Colorado LLT201




Nisida LLT210



Vermont LLT217
























Arizona LLT200



Vulcano LLT211



Madison LLT203

	Standard	Result
 Size	EN ISO 24342	See page opposite
 Thickness	EN ISO 24346	4,5 mm
 Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee*	Light industrial Commercial Residential	10 years 15 years 30 years
 Bevelled edge		No
 Mass	EN ISO 23997	7470 g/m ²
 Standards	EN 649 / EN ISO 10582	Heterogeneous PVC
 Classification	EN 685 / EN ISO 10874: Light industrial Commercial Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987 / EN 423	Excellent
 Light fastness	EN ISO 105-B02	≥7
 Abrasion resistance	EN 649 EN ISO 10582	Group T Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN 434 / EN ISO 23999	≤0,10%
 Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 13 dB
 Indentation - residual	EN 433 / EN ISO 24343-1	Pass ≤0,1 mm
 Castor chair continuous use	EN 425 / EN ISO 4918	Pass
 Thermal resistance	ISO 8302	0,0245 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance**	DIN 51130 EN 13893	R10 DS
VOC emission	Indoor Air Comfort French VOC regulation (ISO 1600) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
 Adhesive	Most applications will not require the use of adhesives. However, we recommend the use of a tackifier for heavy traffic areas.	
 Recycling		Suitable
 Phthalate free		Yes

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.





LOOSE LAY
Karndean
LooseLay

Seattle LT214 and Raven Oak LP302 | 94

Rigid core wood

Our rigid core collection includes a pre-attached acoustic foam backing, that not only eliminates the needs for underlay, but also helps to reduce impact noise transfer, making it perfect for busy restaurants, bars and hotel rooms.

Korlok Wood

Easy to install, Korlok can be fitted over most existing hard floors or imperfect subfloors. This can be beneficial where there is a need to preserve an existing floor or there is limited time to prepare the subfloor. The pre-attached acoustic backing eliminates the need for a separate underlay and reduces impact noise transfer by 21dB, making it ideal for upstairs rooms, apartments and office blocks. With our 5G® fold down click-locking mechanism, Korlok is quick and easy to install, meaning very little downtime during installation. With these added benefits, alongside the intricate designs and durability you expect from Designflooring, Korlok is the perfect choice for a variety of installations.

1420,0mm x 225,0mm



Texas White Ash **RKP8105**



Warm Ash **RKP8103**



Canadian Nude Oak **RKP8117**



Baltic Limed Oak **RKP8111**



Washed Swiss Pine **RKP8113**



Washed Grey Ash **RKP8104**



Canadian Urban Oak **RKP8116**



Smoked Butternut **RKP8107**



Washed Butternut **RKP8108**



























Reclaimed French Oak **RKP8109**



Baltic Washed Oak **RKP8101**



Baltic Mistral Oak **RKP8112**

	Standard	Result
 Size		1420,0mm x 225,0mm
 Thickness	ISO 24346	6,5 mm
 Wear layer	ISO 24340	0,55 mm
Locking system*		5G® fold down installation system
Surface treatment		K-Guard+ PU coating
Guarantee**	Commercial Domestic	15 years 30 years
 Bevelled edge		Micro
 Mass	ISO 23997	7480 g m ⁻²
 Standards	EN 16511	Multilayer modular floorcovering panels
 Classification	EN ISO 10874 Commercial EN ISO 10874 Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	Bfl-s1
 Staining	EN 438-2	Pass (grade 5)
 Light fastness	EN ISO 105-B02	Pass ≥6
 Abrasion resistance	EN13329 Annex E	Pass 4000 cycles
 Furniture chair leg	EN 424	Pass (no visible damage)
 Dimensional stability	BS EN ISO 23999	Pass ≤0.25%
 Swelling	ISO 24336	Pass (0.2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016 EN ISO 10140-3:2010+A1:2015	ΔL _W = 21 dB ΔL _{LIN} = 11 dB
 Indentation - residual	ISO 24343-1	Pass ≤0,1 mm
 Impact resistance	EN13329 Annex F	Pass ≥1800 mm
 Castor chair continuous use	ISO 4918/EN 425	Pass 25000 cycles
 Thermal resistance	ISO 8302	0,052 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance***	EN 13893 DIN 51130	DS R10
 Environmental	Indoor Air Comfort French VOC regulation (ISO 16000) Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification)
 Adhesive	None required; please install according to our installation instructions.	
 Recycling		Suitable
 Phthalate free		Yes

* 5G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

** Subject to terms. Please see our website.

*** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



▷△▽ ■ Baltic Limed Oak RKP8111 | 100





RIGID CORE
Korlok

Palio Core Wood

Palio Core offers a 6,5mm floor thickness including a built-in foam backing to reduce noise transfer to rooms below by up to 19dB. With a 2G™ click-locking mechanism, Palio Core offers quick installation with all the benefits you have come to love and trust from Designflooring products.

1220,0mm x 179,0mm



Sorano **RCP6508**



Bolsena **RCP6507**



Arezzo **RCP6503**



Pisa **RCP6501**



Montieri **RCP6504**



























Vetralla **RCP6506**



Cortono **RCP6510**



Lucca **RCP6509**

	Standard	Result
 Size	ISO 24342	1220,0 mm x 179,0 mm
 Thickness	ISO 24346	6,5 mm
 Wear layer	ISO 24340	0,55 mm
Locking system[^]		2G™ angling installation system
Surface treatment		K-Guard+ PU coating
Guarantee*	Commercial Domestic	15 years 30 years
 Bevelled edge		Micro
 Mass	ISO 23997	7480 g m ⁻²
 Standards	EN 16511	Pass: Multilayer modular floorcovering panels
 Classification	EN ISO 10874 Commercial EN ISO 10874 Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	Br1-s1
 Staining	EN 438-2	Pass (grade 5)
 Light fastness	EN ISO 105-B02	Pass ≥6
 Abrasion resistance	EN13329 Annex E	Pass 4000 cycles
 Furniture chair leg	EN 424	Pass (no visible damage)
 Dimensional stability	BS EN ISO 23999	Pass ≤0,25%
 Swelling	ISO 24336	Pass (0,2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016 EN ISO 10140-3:2010+A1:2015	ΔL _w = 19 dB ΔL _{LIN} = 11 dB
 Indentation - residual	ISO 24343-1	Pass ≤0,1 mm
 Impact resistance	EN13329 Annex F	Pass ≥1800 mm
 Castor chair continuous use	ISO 4918/EN 425	Pass 25000 cycles
 Thermal resistance	ISO 8302	0,052 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance**	EN 13893 DIN 51130	DS R10
 Environmental	Indoor Air Comfort French VOC regulation (ISO 16000) Floorscore SCS-EC10.3-2014 v4.0	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions.
 Adhesive	None required; please install according to our installation instructions.	
 Recycling		Suitable
 Phthalate free		Yes

[^] Produced under licence from Valinge Innovations.

* Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

The 2G™ word mark and logo is a registered trademarks owned by Valinge Innovation AB.



▷△▽ ■ Montieri RCP6504 | 104





Palio
Core

RIGID
CORE

Rigid core stone


Intricate stone designs boasting realistic textures and grain detail.

Korlok Stone

Korlok stone offers a neutral, understated colour tone with a smooth texture finish, enable pairing with any interior, textures and colours.

With acoustic properties of 21dB, noise transfer in office blocks, apartments and co-living environments, is eliminated. The 5G® drop and lock technology, coupled with all the familiar benefits of our rigid core range, makes Korlok a desirable choice for any commercial space.

457,0mm x 600,0mm



Frosted Stone **RKT2401**




Cotswold Stone **RKT2405**













Fossil Grey **RKT2404**



Urban Grey **RKT2402**



Volcanic Black **RKT2406**

	Standard	Result
	Size	457mm x 600mm
	Thickness	ISO 24346 6,5 mm
	Wear layer	ISO 24340 0,55 mm
	Locking system*	5G® fold down installation system
	Surface treatment	K-Guard+ PU coating
	Guarantee**	Commercial Domestic 15 years 30 years
	Bevelled edge	Micro
	Mass	ISO 23997 7480 g m ⁻²
	Standards	EN 16511 Multilayer modular floorcovering panels
	Classification	EN ISO 10874 Commercial EN ISO 10874 Domestic 33: Commercial heavy 23: Domestic heavy
	Reaction to fire	EN 13501-1 Bfl-s1
	Staining	EN 438-2 Pass (grade 5)
	Light fastness	EN ISO 105-B02 Pass ≥6
	Abrasion resistance	EN13329 Annex E Pass 4000 cycles
	Furniture chair leg	EN 424 Pass (no visible damage)
	Dimensional stability	BS EN ISO 23999 Pass ≤0.25%
	Swelling	ISO 24336 Pass (0.2%)
	Acoustic impact noise reduction	EN ISO 10140-1:2016 EN ISO 10140-3:2010+A1:2015 ΔL _W = 21 dB ΔL _{LIN} = 11 dB
	Indentation - residual	ISO 24343-1 Pass ≤0,1 mm
	Impact resistance	EN13329 Annex F Pass ≥1800 mm
	Castor chair continuous use	ISO 4918/EN 425 Pass 25000 cycles
	Thermal resistance	ISO 8302 0,052 m ² K/W Suitable for underfloor heating. Max 27°C
	Slip resistance***	EN 13893 DIN 51130 DS R10
		Indoor Air Comfort Gold certification Compliant low emitting VOC emissions.
	Environmental	French VOC regulation (ISO 16000) A+ Indoor air quality certified; Compliant low emitting VOC emissions. Environmental Product Declaration Product-specific Type III EPD (products with external third-party verification)
		Floorscore SCS-EC10.3-2014 v4.0
	Adhesive	None required; please install according to our installation instructions.
	Recycling	Suitable
	Phthalate free	Yes

* 5G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

** Subject to terms. Please see our website.

*** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



▷△▽ ■ Frosted Stone RKT2401 | 110





RIGID CORE
Korlok

Palio Core Stone

Palio Core tiles by Designflooring, have an acoustic foam backing to reduce impact noise transfer to rooms below by 19dB. With a patented click-locking system and the rigid core technology, it can be installed over uneven subfloors or other hard floors such as ceramic tiles and floorboards, without subfloor imperfections showing.

307,0mm x 600,0mm



Murlo **RCT6302**



























Pienza **RCT6303**



Volterra **RCT6301**



Cetona **RCT6304**

	Standard	Result
 Size	ISO 24342	307,0 mm x 600,0 mm
 Thickness	ISO 24346	6,5 mm
 Wear layer	ISO 24340	0,55 mm
Locking system[^]		2G™ angling installation system
Surface treatment		K-Guard+ PU coating
Guarantee*	Commercial Domestic	15 years 30 years
 Bevelled edge		Micro
 Mass	ISO 23997	7480 g m ⁻²
 Standards	EN 16511	Pass: Multilayer modular floorcovering panels
 Classification	EN ISO 10874 Commercial EN ISO 10874 Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	Bfl-s1
 Staining	EN 438-2	Pass (grade 5)
 Light fastness	EN ISO 105-B02	Pass ≥6
 Abrasion resistance	EN13329 Annex E	Pass 4000 cycles
 Furniture chair leg	EN 424	Pass (no visible damage)
 Dimensional stability	BS EN ISO 23999	Pass ≤0,25%
 Swelling	ISO 24336	Pass (0,2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016 EN ISO 10140-3:2010+A1:2015	ΔL _W = 19 dB ΔL _{LIN} = 11 dB
 Indentation - residual	ISO 24343-1	Pass ≤0,1 mm
 Impact resistance	EN13329 Annex F	Pass ≥1800 mm
 Castor chair continuous use	ISO 4918/EN 425	Pass 25000 cycles
 Thermal resistance	ISO 8302	0,052 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance**	EN 13893 DIN 51130	DS R10
 Environmental	Indoor Air Comfort French VOC regulation (ISO 16000) Floorscore SCS-EC10.3-2014 v4.0	Gold certification Compliant low emitting VOC emissions. A+ Indoor air quality certified; Compliant low emitting VOC emissions.
 Adhesive	None required; please install according to our installation instructions.	
 Recycling		Suitable
 Phthalate free		Yes

[^] Produced under licence from Valinge Innovations.

* Subject to terms. Please see our website.


** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

The 2G™ word mark and logo is a registered trademarks owned by Valinge Innovation AB.



▷△ ■ Cetona RCT6304 | 114





Digital tool suite

To ensure you have everything you need from Designflooring for your projects, visit designflooring.com where you can access our Floorstyle designer tool and Kaleidoscope Floorstyle.

Floorstyle designer tool

Our interactive room viewer, Floorstyle, lets you view our wide range of floors in typical commercial settings.

With improved usability, more sector specific settings, optional colour schemes and side-by-side comparison, you can discover our stylish and highly practical flooring in a truly visual manner.

Try out different glueddown, loose lay and rigid core floor designs in any commercial environment in real time when specifying Designflooring.

Available to use on mobile, tablet or desktop, simply take a photograph or upload an existing room image to get started.

Floorstyle can automatically show any wood, stone or abstract design in a range of laying patterns. You can explore design strips for an authentic finish or add definition, as well as various laying angles.

As well as being able to divide the room and compare different designs you can 'add to favourites' to easily go back.

designflooring.com/floorstyleen



Kaleidoscope Floorstyle

Our sophisticated online Kaleidoscope Floorstyle tool helps specifiers to visualise a bespoke floor design in a commercial setting.


A user-friendly interactive specification program, Floorstyle features all six geometric Kaleidoscope designs - Apex, Cubix, Pyramid, Tripoint, Pennon and Hexa - with over 100 colourways to choose from.

designflooring.com/kalfloorstyleen





△ ▽ ■ Champagne Oak LLP310 | 88



Cleaning and maintenance

Designflooring floors are very hard wearing, but as with any floor they need to be looked after to maintain a finish that will look good for years to come. We recommend following our cleaning and maintenance instructions to help you look after your floor. Visit designflooring.com

Sample service

Our free chip samples will help you narrow down your choice based on colour and tone, while our free full size samples will give you an idea of how each design will look in the your environment.

Order samples at designflooring.com



Get in touch


Contact us for expert advice to help you determine what would work best for your hospitality and leisure space. View case study examples at designflooring.com



Ernest Kukshausen

+49 1707880089

ernest.kukshausen@designflooring.com



Quentin Geraud

0762936678

quentin.geraud@designflooring.com



Richard Bits

+31 613396930

richard.bits@designflooring.com



Kristian Price

+44 7714134086

kristian.price@designflooring.com



Konrad Tenczynski

+48 600180555

konrad.tenczynski@designflooring.com



Marco Cesarii

+34 649395780

marco.cesarii@designflooring.com



Wood products by range - Gluedown

Slip Resistance

RUBENS	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	KP94	Pale Limed Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KP95	Rose Washed Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KP99	Lime Washed Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI05	White Painted Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI31	Grey Scandi Pine	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI32	Washed Scandi Pine	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI33	Natural Scandi Pine	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI34	Washed Sawn Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI35	Soft Sawn Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI36	Coastal Sawn Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI37	Clay Sawn Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI38	Grey Limed Oak	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI39	Raw Spotted Gum	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	KPI40	Nickel Spotted Gum	2mm	0,3mm	No	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	SM-KP95	Rose Washed Oak	2mm	0,3mm	No	R10	B	DS	457,2mm x 76,2mm	96 pieces / 3,34m ²
	SM-KP99	Lime Washed Oak	2mm	0,3mm	No	R10	B	DS	457,2mm x 76,2mm	96 pieces / 3,34m ²
	SM-KPI32	Washed Scandi Pine	2mm	0,3mm	No	R10	B	DS	457,2mm x 76,2mm	96 pieces / 3,34m ²
	SM-KPI38	Grey Limed Oak	2mm	0,3mm	No	R10	B	DS	457,2mm x 76,2mm	96 pieces / 3,34m ²
	PVPI44	Tavolara	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²
	PVPI45	Torcello	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²
	PVPI46	Budelli	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²
	PVPI47	Lampione	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²
	PVPI48	Linosa	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²
	PVPI49	Palmaria	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²
	PVPI50	Levanzo	2mm	0,3mm	No	R10	B	DS	1219,2mm x 177,8mm	22 planks / 4,77m ²

OPUS	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	WP313	Ignea	2,5mm	0,55mm	Micro	R10	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	WP327	Warm Walnut	2,5mm	0,55mm	Micro	R10	C	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	WP329	Bleached Grey Walnut	2,5mm	0,55mm	Micro	R10	C	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	WP330	Tenebra Walnut	2,5mm	0,55mm	Micro	R10	C	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	WP411	Niveus	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP413	Magna	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP414	Argen	2,5mm	0,55mm	Micro	R10	C	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP418	Pallida	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP419	Fabrica	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP420	Stratis	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP421	Rubesco	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP422	Columba	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP423	Avena	2,5mm	0,55mm	Micro	R10	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²

OPUS ENHANCE	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	WP313-SR	Ignea	2,5mm	0,55mm	Micro	R11	B	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	WP411-SR	Niveus	2,5mm	0,55mm	Micro	R11	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP413-SR	Magna	2,5mm	0,55mm	Micro	R11	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP422-SR	Columba	2,5mm	0,55mm	Micro	R11	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²
	WP423-SR	Avena	2,5mm	0,55mm	Micro	R11	B	DS	1219,2mm x 228,6mm	12 planks / 3,34m ²

VAN GOGH	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	VGW52T	Auckland Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW80T	White Washed Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW81T	Country Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW82T	Distressed Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW83T	Frosted Birch	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW84T	Birch	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW85T	French Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW86T	Classic Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW89T	Ebony	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGW94T	Honey Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGWI00T	Aged Redwood	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	VGWI02T	Charred Oak	3mm	0,55mm	Micro	R10	B	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²

ART SELECT	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	AP01	Blond Oak	3mm	0,7mm	Standard	R10	A	DS	228,6mm x 76,2mm	192 planks / 3,34m ²
	AP07	Storm Oak	3mm	0,7mm	Standard	R10	A	DS	228,6mm x 76,2mm	192 planks / 3,34m ²
	EW03	Hickory Nutmeg	3mm	0,7mm	Standard	R10	C	DS	914,4mm x 152,4mm	24 planks / 3,34m ²
	RL01	Spring Oak	3mm	0,7mm	Standard	R10	A	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	RL02	Summer Oak	3mm	0,7mm	Standard	R10	A	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²
	RL12	Storm Oak	3mm	0,7mm	Standard	R10	A	DS	1219,2mm x 177,8mm	15 planks / 3,25m ²

Wood products by range - Loose lay

LOOSELAY	Code	Product Name	Thickness	Wear Layer	Bevel	Slip Resistance			Size	Box Quantity
						DIN 51130	DIN 51097	EN 13893		
	LLP92	Country Oak	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP95	Ashland	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP99	Hudson	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP101	Traditional Oak	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP102	Heritage Oak	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP106	Antique Timber	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP108	Providence	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP109	Stamford	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP112	Hartford	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP113	Cambridge	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP142	Sicilia	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP143	Sardinia	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP144	Tavolara	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP145	Torcello	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP146	Budelli	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP147	Lampione	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP148	Linosa	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP149	Palmaria	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP150	Levano	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP151	Vivara	4,5mm	0,55mm	No	R10	B	DS	1050,0mm x 250,0mm	12 planks / 3,15m ²
	LLP301	Twilight Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP302	Raven Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP303	Antique Heart Pine	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP304	Weathered Heart Pine	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP305	Reclaimed Heart Pine	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP306	Pearl Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP307	Neutral Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP308	French Grey Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP309	Taupe Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP310	Champagne Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP311	Bleached Tasmanian Oak	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²
	LLP317	Lemon Spotted Gum	4,5mm	0,55mm	No	R10	B	DS	1500,0mm x 250,0mm	8 planks / 3m ²

Wood products by range - Rigid core

KORLOK	Code	Product Name	Thickness	Wear Layer	Bevel	Slip Resistance			Size	Box Quantity
						DIN 51130	DIN 51097	EN 13893		
	RKP8101	Baltic Washed Oak	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8103	Warm Ash	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8104	Washed Grey Ash	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8105	Texas White Ash	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8107	Smoked Butternut	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8108	Washed Butternut	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8109	Reclaimed French Oak	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8111	Baltic Limed Oak	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8112	Baltic Mistral Oak	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8113	Washed Swiss Pine	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8116	Canadian Urban Oak	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²
	RKP8117	Canadian Nude Oak	6,5mm	0,55mm	Micro	R10	-	DS	1420,0 x 225,0mm	10 planks / 3,195m ²

PALIO CORE	Code	Product Name	Thickness	Wear Layer	Bevel	Slip Resistance			Size	Box Quantity
						DIN 51130	DIN 51097	EN 13893		
	RCP6501	Pisa	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6503	Arezzo	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6504	Montieri	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6506	Vetralla	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6507	Bolsena	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6508	Sorano	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6509	Lucca	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²
	RCP6510	Cortono	6,5mm	0,55mm	Micro	R10	-	DS	1220,0mm x 179,0mm	10 planks / 2,18m ²

Stone products by range - **Gluedown**

Slip Resistance										
RUBENS	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	ST15	Black Riven Slate	2mm	0,3mm	No	R10	C	DS	304,8mm x 457,2mm	24 tiles / 3,34m ²
	ST16	Grey Riven Slate	2mm	0,3mm	No	R10	C	DS	304,8mm x 457,2mm	24 tiles / 3,34m ²
	ST17	Honed Oyster Slate	2mm	0,3mm	No	R10	C	DS	304,8mm x 457,2mm	24 tiles / 3,34m ²
OPUS	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	SP213	Urbus	2,5mm	0,55mm	Micro	R10	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP215	Ferra	2,5mm	0,55mm	Micro	R10	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP216	Fumo	2,5mm	0,55mm	Micro	R10	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP217	Argento	2,5mm	0,55mm	Micro	R10	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP218	Lutum	2,5mm	0,55mm	Micro	R10	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
OPUS ENHANCE	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	SP213-SR	Urbus	2,5mm	0,55mm	Micro	R11	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP216-SR	Fumo	2,5mm	0,55mm	Micro	R11	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP217-SR	Argento	2,5mm	0,55mm	Micro	R11	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²
	SP218-SR	Lutum	2,5mm	0,55mm	Micro	R11	C	DS	457,2mm x 609,6mm	12 tiles / 3,34m ²

Stone products by range - **Loose lay**

Slip Resistance										
LOOSELAY	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	LLT200	Arizona	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT201	Colorado	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT202	Indiana	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT203	Madison	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT208	Tino	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT209	Capri	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT210	Nisida	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT211	Vulcano	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT214	Seattle	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT215	Alaska	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT216	Utah	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT217	Vermont	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT218	Ontario	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²
	LLT219	Quebec	4,5mm	0,55mm	No	R10	A	DS	500,0mm x 610,0mm	10 tiles / 3,05m ²

Stone products by range - **Rigid core**

Slip Resistance										
KORLOK	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	RKT2401	Frosted Stone	6,5mm	0,55mm	Micro	R10	-	DS	457,0 x 600,0mm	10 tiles / 2,742m ²
	RKT2402	Urban Grey	6,5mm	0,55mm	Micro	R10	-	DS	457,0 x 600,0mm	10 tiles / 2,742m ²
	RKT2404	Fossil Grey	6,5mm	0,55mm	Micro	R10	-	DS	457,0 x 600,0mm	10 tiles / 2,742m ²
	RKT2405	Cotswold Stone	6,5mm	0,55mm	Micro	R10	-	DS	457,0 x 600,0mm	10 tiles / 2,742m ²
	RKT2406	Volcanic Black	6,5mm	0,55mm	Micro	R10	-	DS	457,0 x 600,0mm	10 tiles / 2,742m ²
PALIO CORE	Code	Product Name	Thickness	Wear Layer	Bevel	DIN 51130	DIN 51097	EN 13893	Size	Box Quantity
	RCT6301	Volterra	6,5mm	0,55mm	Micro	R10	-	DS	307,0mm x 600,0mm	10 tiles / 1,84m ²
	RCT6302	Murlo	6,5mm	0,55mm	Micro	R10	-	DS	307,0mm x 600,0mm	10 tiles / 1,84m ²
	RCT6303	Pienza	6,5mm	0,55mm	Micro	R10	-	DS	307,0mm x 600,0mm	10 tiles / 1,84m ²
	RCT6304	Cetona	6,5mm	0,55mm	Micro	R10	-	DS	307,0mm x 600,0mm	10 tiles / 1,84m ²

Solid colours - Gluedown

SOLID COLOURS	Code	Product Name	Thickness	Wear Layer	Bevel	Slip Resistance			Size	Box Quantity
						DIN 51130	DIN 51097	EN 13893		
	V11	Baby Blue	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V12	Crimson	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V13	Azure	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V14	Taupe	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V15	Laurel	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V16	Terracotta	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V17	Blush	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V18	Dove Grey	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V19	Gold	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke
	V20	Lace	3,0mm	0,7mm	Micro	R10	–	DS	Bespoke	Bespoke





Designflooring

Designflooring

T: +44 1386 820105

F: +44 1386 820132

E: info@designflooring.com

Designflooring SAS

T : 01 57 32 39 13

F : 01 57 32 39 14

E: ventes@designflooring.com

Designflooring GmbH

T: 0211 469 59203

F: 0211 469 59204

E: verkauf@designflooring.com

Designflooring Nederland

T: 020 200 8282

F: 020 200 8386

E: verkoop@designflooring.com



designflooring.com