

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2,0 mm
Wear layer	EN ISO 24340	0,3 mm
Surface treatment		K-Guard+ PU coating
Guarantee <sup>1</sup>	Commercial	10 years
	Residential	30 years
Bevelled edge		No
Mass per unit area	EN ISO 23997	3605 g/m <sup>2</sup>
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Commercial	31: Commercial moderate
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 660-2	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 1 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0084 m <sup>2</sup> K/W
		Suitable for underfloor heating. Max 27°C
Slip resistance <sup>2</sup>	EN 13893	DS
	DIN 51130	R10
Adhesive	Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature+	Yes
	Pressure Sensitive	Yes
Environmental	French VOC regulation (ISO 16000)	A+
	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions.
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	DIBt/AgBB	Pass
Recycling		Suitable
Phthalate free		Yes

<sup>1</sup> Subject to terms see website.

<sup>2</sup> Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

**For more information:**

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)



EN 14041: 2004 (DOP 2017/RU/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/31 Manufactured to ISO 10582





	Product Code	Size		Box Quantity		Slip Resistance DIN 51130
		mm	inches	m <sup>2</sup>	Pieces	
Wood Designs	KP94	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP95	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP96	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP97	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP99	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP104	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP105	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP131	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP132	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP133	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP134	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP135	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP136	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP137	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP138	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP139	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	KP140	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	PVP144	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10
	PVP145	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10
	PVP146	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10
PVP147	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10	
PVP148	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10	
PVP149	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10	
PVP150	1219,2 x 177,8	48" x 7"	4,769	22 Planks	R10	
SM-KP132	457,2 x 76,2	18" x 3"	3,345	96 Planks	R10	
SM-KP138	457,2 x 76,2	18" x 3"	3,345	96 Planks	R10	
SM-KP95	457,2 x 76,2	18" x 3"	3,345	96 Planks	R10	
SM-KP99	457,2 x 76,2	18" x 3"	3,345	96 Planks	R10	
Stone Designs	ST13	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST14	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST15	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST16	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST17	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10

