

	Standard	Result
Size	EN ISO 24342	1500,0 x 250,0 mm
Thickness	EN ISO 24346	4,5 mm
Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee¹	Light industrial	15 years
	Commercial	15 years
	Residential	30 years
Bevelled edge		No
Mass per unit area	EN ISO 23997	7470 g/m ²
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Light industrial	42: Light industrial general
	EN 685/EN ISO 10874 - Commercial	33: Commercial heavy
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 7)
Abrasion resistance	EN 660-2	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,10%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 13 dB
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0245 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance²	EN 13893 DIN 51130	D5 R10
Adhesive		Most applications will not require the use of adhesives. However, we recommend the use of a tackifier for heavy traffic areas.
Environmental	French VOC regulation (ISO 16000)	A+
	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions.
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
EPD	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms see website.

² Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

For more information:

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: info@designflooring.com

www.designflooring.com



EN 14041: 2004 (DOP 2017/LLLB/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582



Product Code	Size		Box Quantity		Slip Resistance
	mm	inches	m ²	Pieces	DIN 51130
LLP301	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP302	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP303	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP304	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP305	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP306	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP307	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP308	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP309	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP310	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP311	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10
LLP317	1500,0 x 250,0	59,06" x 9,84"	3,000	8 Planks	R10

Wood Designs