

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2,0 mm
Wear layer	EN ISO 24340	0,3 mm
Surface treatment		K-Guard+ PU coating
Guarantee <sup>1</sup>	Commercial	10 years
	Residential	30 years
Bevelled edge		No
Mass per unit area	EN ISO 23997	3605 g/m <sup>2</sup>
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Commercial	31: Commercial moderate
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 660-2	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 1 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0084 m <sup>2</sup> K/W
		Suitable for underfloor heating. Max 27°C
Slip resistance <sup>2</sup>	EN 13893	DS
	DIN 51130	R10
Adhesive		Please refer to our recommended adhesive list
Environmental	French VOC regulation (ISO 16000)	A+
	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions.
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	DIBt/AgBB	Pass
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

<sup>1</sup> Subject to terms see website.

<sup>2</sup> Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

**For more information:**

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14


Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)

06/22



	Product Code	Size		Box Quantity		Slip Resistance DIN 51130
		mm	inches	m <sup>2</sup>	Pieces	
Wood Designs	CH-KP156	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	CH-KP95	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	KP94-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP95-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP96-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP97-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP99-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP104-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP105-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP131-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP132-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP138-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP144-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP146-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP147-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP152-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
	KP154-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10
KP155-7	1219,2 x 177,8	48" x 7"	4,335	20 Planks	R10	
Stone Designs	ST14	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST16	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST22	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10
	ST26	304,8 x 457,2	12" x 18"	3,345	24 Tiles	R10